

DIN 1835B



$\lambda=30^\circ$


$\gamma=10^\circ$

typ

HR P



Použití - Usage - Applikation - Употребление



HSSE- PM

HSS Co8

	3	5	6	8	10		13
	3	5	6	8	10		

HSSE
 PM

HSS
 Co8

D k 12	l	L	d h 6	Z	CODE 128517P+AlTiN	CODE 128518P	IDENT.
6	13	57	6	4	•	•	.060
7	16	66	10	4		•	.070
8	19	69	10	4	•	•	.080
9	19	69	10	4		•	.090
10	22	72	10	4	•	•	.100
11	22	79	12	4		•	.110
12	26	83	12	4	•	•	.120
13	26	83	12	4		•	.130
14	26	83	12	4	•	•	.140
15	26	83	12	4		•	.150
16	32	92	16	4	•	•	.160
17	32	92	16	4		•	.170
18	32	92	16	4	•	•	.180
20	38	104	20	4	•	•	.200
22	38	104	20	5		•	.220
24	45	121	25	5		•	.240
25	45	121	25	5		•	.250
26	45	121	25	5		•	.260
28	45	121	25	5		•	.280
30	45	121	25	5		•	.300
32	53	133	32	6		•	.320



128517P - Dodáváme s AlTiN povlakem - AlTiN coated - Lieferbar mit der Beschichtung AlTiN
 - Поставляем с AlTiN покрытием

Příklad objednávky - Example of order - Bestellsungsbeispiel - Пример заказа

128517P.060 + AlTiN

128518P.060 + TiN